



Rundlitzenseil
Round strand ropes

Cables de cordones redondos
Câbles à torons ronds

6 x 19 Seale (1+9+9) + FC
DIN 3058

Nr./No.	Nenn-durch-messer Nom. diameter Ø mm	Gewicht weight peso poids ca. kg/m	rechn. Bruchkraft calculated aggregate break.load carga de rotura calculada charge de rupture calculée		Mindesbruchkraft minimum breaking load carga de rotura minima charge de rupture minimum	
			1770 N/mm ² 180 kp/mm ²		1770 N/mm ² 180 kp/mm ²	
			kN	kp	kN	kp
01051-060	6	0,134	24,5	2490	21,1	2140
01051-070	7	0,183	33,4	3390	28,7	2920
01051-080	8	0,238	43,6	4430	37,5	3810
01051-090	9	0,302	55,2	5610	47,4	4830
02051-100	10	0,373	68,1	6930	58,6	5960
02051-110	11	0,451	82,4	8380	70,9	7210
02051-120	12	0,537	98,1	9980	84,3	8580
02051-130	13	0,630	115	11700	99	10100
02051-140	14	0,730	134	13600	115	11700
02051-150	15	0,838	153	15600	132	13400
02051-160	16	0,954	174	17700	150	15300
02051-170	17	1,080	197	20000	169	17200
02051-180	18	1,210	221	22400	190	19300
02051-190	19	1,350	246	25000	211	21500
02051-200	20	1,490	272	27700	234	23800
02051-220	22	1,800	330	33500	283	28800
02051-240	24	2,150	392	39900	337	34300
02051-260	26	2,520	460	46800	396	40300
02051-280	28	2,920	534	54300	459	46700
02051-320	32	3,820	698	71000	600	61000
02051-360	36	4,830	883	89800	759	77200

FC = Fasereinlage - fibre core - alma textil - âme textile
SEL = Stahleinlage Litze - wire strand core (WSC) - alma metálica - âme métallique
SES = Stahleinlage Seil - independent wire rope core (IWRC) - alma metálica cablada - âme métallique câblée
Technische Änderung vorbehalten / Technical alterations reserved