



Rundlitzenseil
Round strand ropes

Cables de cordones redondos
Câbles à torons ronds

6 x 19 Standard (1+6+12) + IWRC
DIN 3060

	Nenndurch- messer Nom. diameter Ø	Gewicht weight peso poids	rechn. Bruchkraft calculated aggregate break.load carga de rotura calculada charge de rupture calculée		Mindesbruchkraft minimum breaking load carga de rotura mínima charge de rupture minimum	
Nr./No.	mm	ca. kg/m	1770 N/mm ² 180 kp/mm ²		1770 N/mm ² 180 kp/mm ²	
			kN	kp	kN	kp
01081-030	3	0,0342	6,6	672	5,29	538
01081-040	4	0,0609	11,7	1190	9,40	956
01081-050	5	0,0952	18,3	1870	14,70	1490
01081-060	6	0,1380	26,4	2690	21,20	2150
01081-070	7	0,1870	36,0	3650	28,80	2930
01081-080	8	0,2430	47,0	4780	37,60	3820
01081-090	9	0,3080	59,4	6040	47,60	4840
02081-100	10	0,3810	73,4	7460	58,80	5970
02081-110	11	0,4610	88,8	9020	71,10	7230
02081-120	12	0,5480	106	10700	84,60	8610
02081-130	13	0,6430	124	12600	99,30	10100
02081-140	14	0,7460	144	14600	115	11700
02081-160	16	0,9740	188	19100	150	15300
02081-180	18	1,2300	238	24100	190	19300
02081-200	20	1,5200	293	29800	235	23900
02081-220	22	1,8400	355	36100	284	28900
02081-240	24	2,1900	423	42900	338	34500
02081-260	26	2,5700	496	50500	397	40400
02081-280	28	2,9800	575	58500	461	46900
02081-320	32	3,9000	751	76400	602	61100
02081-360	36	4,9300	951	96700	761	77400
02081-400	40	6,0900	1170	119000	940	95600
02081-440	44	7,3700	1420	145000	1140	116000
02081-480	48	8,7700	1690	172000	1350	137000
02081-520	52	10,3000	1980	202000	1590	162000
02081-560	56	12,0000	2300	234000	1840	187000

FC = Fasereinlage - fibre core - alma textil - âme textile

SEL = Stahleinlage Litze - wire strand core (WSC) - alma metálica - âme métallique

SES = Stahleinlage Seil - independent wire rope core (IWRC) - alma metálica cablada - âme métallique câblée

Technische Änderung vorbehalten / Technical alterations reserved