



Rundlitzenseil
Round strand ropes

Cables de cordones redondos
Câbles à torons ronds

6 x 37 (1+6+12+18) + FC
DIN 3066

Nr./No.	Nenndurchmesser Nom. diameter Ø mm	Gewicht weight peso poids ca. kg/m	rechn. Bruchkraft calculated aggregate break.load carga de rotura calculada charge de rupture calculée		Mindesbruchkraft minimum breaking load carga de rotura minima charge de rupture minimum	
			1770 N/mm ² 180 kp/mm ²		1770 N/mm ² 180 kp/mm ²	
			kN	kp	kN	kp
01043-060	6	0,125	22,8	2320	18,8	1910
01043-070	7	0,170	31,0	3150	25,6	2600
01043-080	8	0,221	40,5	4120	33,4	3400
01043-090	9	0,280	51,2	5210	42,3	4300
02043-100	10	0,346	63,3	6430	52,2	5310
02043-110	11	0,419	76,5	7780	63,1	6420
02043-120	12	0,498	91,1	9260	75,1	7640
02043-130	13	0,585	107	10900	88,2	8970
02043-140	14	0,678	124	12600	102	10400
02043-160	16	0,886	162	16500	134	13600
02043-180	18	1,120	205	20800	169	17200
02043-200	20	1,380	253	25700	209	21200
02043-220	22	1,670	306	31100	253	25700
02043-240	24	1,990	364	37100	301	30600
02043-260	26	2,340	428	43500	353	35900
02043-280	28	2,710	496	50400	409	41600
02043-320	32	3,540	648	65900	534	54300
02043-360	36	4,480	820	83400	676	68800
02043-400	40	5,540	1010	103000	835	84900
02043-440	44	6,700	1220	125000	1010	103000
02043-480	48	7,970	1460	148000	1200	122000
02043-520	52	9,360	1710	174000	1410	144000
02043-560	56	10,900	1980	202000	1640	166000
02043-600	60	12,500	2280	232000	1880	191000
02043-640	64	14,200	2590	263000	2140	217000

FC = Fasereinlage - fibre core - alma textil - âme textile
SEL = Stahleinlage Litze - wire strand core (WSC) - alma metálica - âme métallique
SES = Stahleinlage Seil - independent wire rope core (IWRC) - alma metálica cablada - âme métallique câblée
Technische Änderung vorbehalten / Technical alterations reserved